

ALTAVOZ DE TECHO CON CAJA POSTERIOR

A-254ATC

4"

6 W

99 dB

Altavoz para empotrar en techo con reja circular metálica, cerco y caja posterior de ABS. Anclaje es mediante muelles.



Altavoz	4"
Potencia RMS	6 W
Selección de potencia	6, 3 y 1 W
Respuesta en frecuencia	150 ~ 18.000 Hz
SPL 1 m, 1 kHz	91 dB (1 W) / 99 dB (6 W)
Dimensiones (mm)	Ø 140 x 130 (fondo).
Orificio para empotrar	Ø 125 mm
Peso	0,90 kg
Acabado	ABS y metal blanco RAL 9016



A254ATC_ES

C/ Barcelona 101
17003 Girona (Spain)
(+34) 972 203 300

OPTIMUS
SOUND & COMMUNICATION



CEILING LOUDSPEAKER WITH REAR BOX

A-254ATC

4"

6 W

99 dB

A loudspeaker for flush installation in the ceiling with a circular metal grille, surround and rear box in ABS. Spring mounting system.



Loudspeaker	4"
RMS power	6 W
Power selection	6, 3 and 1 W
Frequency response	150 ~ 18,000 Hz
SPL 1 m, 1 kHz	91 dB (1 W)/99 dB (6 W)
Dimensions (mm)	Ø 140 x 130 (depth)
Hole for flush installation	Ø 125 mm
Weight	0.90 Kg
Finish	ABS and RAL 9016 white metal



A254ATC_EN

C/ Barcelona 101
17003 Girona (Spain)
(+34) 972 203 300

 **OPTIMUS**
SOUND & COMMUNICATION

