

SUBWOOFER DE TECHO

A-258SB

Altavoz de techo para reproducción de graves, con altavoz de 8" y 50 W de potencia RMS, elevada presión acústica (hasta 107 dB) y con posibilidad de conexión a 8 ohm y en línea de 100 V. Adecuado como refuerzo de graves en cualquier instalación de megafonía.



Altavoz	8"
Potencia RMS	50 W (100 W programa)
Selección	100 V, 8 Ω , OFF
Sensibilidad	90 dB SPL (1 W, 1m, 1 kHz)
Presión acústica	107 dB SPL (50 W, 1m, 1 kHz)
Respuesta en frecuencia	50 ~ 200 Hz
Orificio a empotrar	\varnothing 250 mm
Grosor del techo	10 ~ 35 mm
Dimensiones (mm)	\varnothing 280 x 192 (fondo)
Peso	4 kg
Acabado	ABS y rejilla metálica
Color	blanco RAL9003
Montaje	lengüetas rotatorias



CEILING SUBWOOFER

A-258SB

Ceiling speaker for low frequencies reproduction, with 8" speaker and 50 W RMS power, high sound pressure level (up to 107 dB) and with the possibility of connection to 8 ohms and 100 V line. Suitable as bass reinforcement in any public address installation.



Loudspeaker	8"
Rated power (RMS)	50 W (100 W program)
Selection	100 V, 8 Ω, OFF
Sensitivity	90 dB SPL (1 W, 1m, 1 kHz)
Sound pressure	107 dB SPL (50 W, 1m, 1 kHz)
Frequency range	50 ~ 200 Hz
Cutout size	Ø 250 mm
Ceiling thickness	10 ~ 35 mm
Dimensions (mm)	Ø 280 x 192 (depth)
Weight	4 kg
Finish	ABS and metallic grille
Colour	white RAL9003
Mounting	rotary tabs

