

## ALTAVOCES EXPONENCIALES SERIE AC-600

**AC-615T**

**15 W** **119 dB**

**AC-630T**

**30 W** **124 dB**

**AC-650T**

**50 W** **126 dB**

Altavoces exponenciales de boca circular fabricados en aluminio y acero para línea de 100 V y con toma de baja de impedancia.

**IP66**

AC-615T



AC-650T



AC-630T



	<b>AC-615T</b>	<b>AC-630T</b>	<b>AC-650T</b>
Potencia RMS	15 W	30 W	50 W
Selección de potencia	15, 7,5, 3,75 y 1,9 W   8 ohm	30, 15, 7,5 y 3,8 W   8 ohm	50, 25, 12,5 y 6,25   16 ohm
SPL 1 m, 1 kHz	107 dB (1 W) / 119 dB (15 W)	109 dB (1 W) / 124 dB (30 W)	109 dB (1 W) / 126 dB (50 W)
Respuesta en frecuencia	300 ~ 10.000 Hz	380 ~ 10.000 Hz	380 ~ 6.500 Hz
Grado de protección	IP66 (IEC-529)	IP66 (IEC-529)	IP66 (IEC-529)
Dimensiones (mm)	Ø 207 x 245	Ø 246 x 292	Ø 327 x 350
Peso	1,3 kg	2,1 kg	2,8 kg
Acabado	aluminio y acero	aluminio y acero	aluminio y acero

# LOUDSPEAKERS

## EXPONENTIAL LOUDSPEAKERS SERIES AC-600

**AC-615T**

**15 W** **119 dB**

**AC-630T**

**30 W** **124 dB**

**AC-650T**

**50 W** **126 dB**

Exponential loudspeakers with a circular mouth made in aluminium and steel. 100 V line and low impedance connection.

**IP66**

AC-615T



AC-650T



AC-630T



	<b>AC-615T</b>	<b>AC-630T</b>	<b>AC-650T</b>
RMS power	15 W	30 W	50 W
Power selection	15, 7.5, 3.75 & 1.9 W   8 ohm	30, 15, 7.5 & 3.8 W   8 ohm	50, 25, 12.5 & 6.25   16 ohm
SPL 1 m, 1 kHz	107 dB (1 W) / 119 dB (15 W)	109 dB (1 W) / 124 dB (30 W)	109 dB (1 W) / 126 dB (50 W)
Frequency response	300 ~ 10.000 Hz	380 ~ 10.000 Hz	380 ~ 6.500 Hz
Protection	IP66 (IEC-529)	IP66 (IEC-529)	IP66 (IEC-529)
Dimensions (mm)	Ø 207 x 245	Ø 246 x 292	Ø 327 x 350
Weight	1.3 kg	2.1 kg	2.8 kg
Finish	aluminium and steel	aluminium and steel	aluminium and steel