

INTERCOMUNICACIÓN

Intercomunicador industrial IP/SIP



JR202-CB-SIP » IP55 · IK10

Intercomunicador antivándalo y resistente a la intemperie. La carcasa está realizada con acero laminado en frío y proporciona una elevada protección contra el polvo y la entrada de humedad. Incorpora un auricular telefónico realizado con ABS, con cable espiral de acero inoxidable. La marcación es automática, preprogramada al descolgar.



Método de llamada	Descolgar auricular (marcación automática)
Comunicación de audio	Auricular, full duplex
Antivándalo	Si
Alimentación	PoE o 12V DC
Consumo	1,8 W máx
Protocolo SIP	SIP 2.0 (RFC3261)
Codecs	G.711 A/U, G.7231G h/l, G.729, G.722, G.726
Volumen de llamada	80 dB(A) @ 1 m
Grado de protección	IP 55 @ EN60529
Rango de temperaturas	-30°C a +65°C
Material envolvente	Acero laminado en frío
Material auricular	ABS con cable espiral de acero inoxidable
Color	Gris
Dimensiones (mm)	100 x 240 x 106
Peso	2,7 kg

Equipo resistente a climatología adversa y al vandalismo, diseñado para ser utilizado en aparcamientos, centros penitenciarios, andenes de estaciones de ferrocarril y metro, comisarías de policía, cajeros automáticos, estadios deportivos, exterior de edificios...

INTERCOMMUNICATION

IP/SIP industrial intercom



JR202-CB-SIP » IP55 · IK10

Anti-vandalism and weather resistant intercom. Equipment is made with cold rolled steel that provides high protection against dust and moisture. It incorporates a telephone handset made with ABS and a stainless steel spiral cable, with a keypad to make calls to pre-programmed numbers (9) or to any other number.



Calling method	Pick up handset (automatic dialing)
Audio communication	Handset, full duplex
Anti-vandalism	yes
Power supply	PoE or 12V DC
Consumption	1.8 W max
SIP protocol	SIP 2.0 (RFC3261)
Codecs	G.711 A/U, G.7231G h/l, G.729, G.722, G.726
Call volume	80 dB(A) @ 1 m
Protection degree	IP 55 @ EN60529
Temperature range	-30°C to +65°C
Chassis material	Cold rolled steel
Handset material	ABS with stainless steel spiral cable
Colour	Grey
Dimensions (mm)	100 x 240 x 106
Weight	2.7 kg

Equipment resistant to adverse weather conditions and vandalism, designed to be used in car parks, prisons, railway and metro station platforms, police stations, ATMs, sports stadiums, outside buildings...