



ATENUADORAS DE 4, 40 y 100 W

SERIE AV

Atenuadoras de volumen para altavoces de línea de 100 V. Disponen de la función de seguridad de avisos, para difusión de avisos a máxima potencia incluso con la atenuadora cerrada. Disponibles modelos de 4 W, 40 W y 100 W sin selección de programa, y de 4 W y 40 W con selector de programa musical.

AV-4E



AV-40E / AV-100



AV-4P / AV-40P



	AV-4E	AV-40E / AV-100	AV-4P / AV-40P
Entrada	1 x línea de 100 V	1 x línea de 100 V	6 x línea de 100 V
Salida	1 x línea de 100 V	1 x línea de 100 V	1 x línea de 100 V
Potencia regulada	Hasta 4 W	Hasta 40 W / 100 W	Hasta 4 W / 40 W
Control de volumen	en 6 fracciones	en 6 fracciones	en 6 fracciones
Seguridad de avisos	tres hilos (+, S y -C)	tres hilos (+, S y -C)	cuatro hilos (relé de prioridad)
Selección de canal	-	-	hasta 6 canales
Dimensiones (mm)	78 x 78 x 50	150 x 78 x 50	150 x 78 x 50
Peso	90 g	360 g / 650 g	190 g / 325 g
Acabado	ABS blanco	ABS blanco	ABS blanco
Montaje	en caja universal	en caja universal	en caja universal

MPP-01 / MPP-02

Relé de seguridad de avisos, para amplificadores que no incluyan esta función. El modelo MPP-01 es un módulo autónomo y se alimenta a 230 V CA, adecuado para amplificadores que no vayan en rack. El modelo MPP-02 es de carril DIN, se alimenta a 24 V CC y es adecuado para equipos instalados en rack.





4, 40 and 100 W ATTENUATORS

AV SERIES

Volume attenuators for 100-V line loudspeakers. They have announcement security function for announcements broadcasting at maximum power even with the attenuator closed. Available models of 4 W, 40 W and 100 W without program selection, and 4 W and 40 W with musical program selector.

AV-4E



AV-40E / AV-100



AV-4P / AV-40P



AV-4E

Input	1 x 100-V line
Output	1 x 100-V line
Adjusted power	Up to 4 W
Volume control	in 6 fractions
Announcement security	three lines (+, S and -C)
Channel selection	-
Dimensions (mm)	78 x 78 x 50
Weight	90 g
Finish	White ABS
Mounting	in universal box

AV-40E / AV-100

Input	1 x 100-V line
Output	1 x 100-V line
Adjusted power	Up to 40 W/100 W
Volume control	in 6 fractions
Announcement security	three lines (+, S and -C)
Channel selection	-
Dimensions (mm)	150 x 78 x 50
Weight	360 g/650 g
Finish	White ABS
Mounting	in universal box

AV-4P / AV-40P

Input	6 x 100-V line
Output	1 x 100-V line
Adjusted power	Up to 4 W/40 W
Volume control	in 6 fractions
Announcement security	four lines (priority relay)
Channel selection	-
Dimensions (mm)	150 x 78 x 50
Weight	190 g/325 g
Finish	White ABS
Mounting	in universal box

MPP-01/MPP-02

Announcement security relay for amplifiers not including this function. The MPP-01 is an autonomous model and is powered at 230 Vac, suitable for amplifiers not in a rack. The MPP-02 is DIN rail, powered at 24 Vdc and is suitable for units installed in rack.

