

ATENUADORAS DE 4, 12, 40 y 60 W

SERIE CV Las atenuadoras CV regulan la entrega de potencia con un conmutador rotatorio, con 6 posiciones de atenuación y otras 6 de enmudecimiento de la señal. Disponen de función de seguridad de avisos, y los modelos de 12, 40 y 60 W disponen de transformador, adecuados para sistemas con supervisión de líneas de altavoces.

El selector CV admite 6 entradas de línea de 100 V y utiliza un conmutador rotatorio para seleccionar una de ellas.



CV-4WE + M-420W

	atenuadora CV	selector CV-P
Entrada	1 x línea de 100 V	6 x línea de 100 V
Salida	1 x línea de 100 V	1 x línea de 100 V
Potencia regulada	4 / 12 / 40 / 60 W máximo	-
Control de volumen	en 6 fracciones	-
Selección de canal	-	hasta 6 canales
Seguridad de avisos	sí	sí
Alimentación	24 V CC	24 V CC
Consumo	10 mA	10 mA
Acabado	blanco, marfil, plata, grafito	blanco, marfil, plata, grafito
Montaje	en caja universal	en caja universal

MODELOS

Marfil

CV-4IE Atenuadora de 4 W (sin marco)
 CV-12I Atenuadora de 12 W (sin marco)
 CV-40IE Atenuadora de 40 W (sin marco)
 CV-60I Atenuadora de 60 W (sin marco)
 CV-PI Selector 6 programas (sin marco)
 M-420I Marco embellecedor

Grafito


CV-4BE Atenuadora de 4 W (sin marco)
 CV-12B Atenuadora de 12 W (sin marco)
 CV-40BE Atenuadora de 40 W (sin marco)
 CV-60B Atenuadora de 60 W (sin marco)
 CV-PB Selector 6 programas (sin marco)
 M-420B Marco embellecedor

Blanco

CV-4WE Atenuadora de 4 W (sin marco)
 CV-12W Atenuadora de 12 W (sin marco)
 CV-40WE Atenuadora de 40 W (sin marco)
 CV-60W Atenuadora de 60 W (sin marco)
 CV-PW Selector 6 programas (sin marco)
 M-420W Marco embellecedor

Plata

CV-4SE Atenuadora de 4 W (sin marco)
 CV-12S Atenuadora de 12 W (sin marco)
 CV-40SE Atenuadora de 40 W (sin marco)
 CV-60S Atenuadora de 60 W (sin marco)
 CV-PS Selector 6 programas (sin marco)
 M-420S Marco embellecedor



4, 12, 40 and 60 W ATTENUATORS

CV SERIES The CV attenuators adjust the power delivery with a rotating switch with 6 attenuation positions and another 6 for silencing the signal. They have announcement security function, and the 12, 40 and 60 W models a transformer, suitable for systems with loudspeaker line supervision.

The CV selector supports 6 100-V line inputs and uses a rotating switch to select one of them.



CV-4WE + M-420W

	atenuadora CV	selector CV-P
Input	1 x 100-V line	6 x 100-V line
Output	1 x 100-V line	1 x 100-V line
Adjusted power	4 / 12 / 40 / 60 W maximum	-
Volume control	in 6 fractions	-
Channel selection	-	up to 6 channels
Announcement security	yes	yes
Power supply	24 Vdc	24 Vdc
Consumption	10 mA	10 mA
Finish	white, ivory, silver, graphite	white, ivory, silver, graphite
Mounting	in universal box	in universal box

MODELS

Ivory	Graphite	White	Silver
CV-4IE 4 W attenuator (without frame)	CV-4BE 4 W attenuator (without frame)	CV-4WE 4 W attenuator (without frame)	CV-4SE 4 W attenuator (without frame)
CV-12I 12 W attenuator (without frame)	CV-12B 12 W attenuator (without frame)	CV-12W 12 W attenuator (without frame)	CV-12S 12 W attenuator (without frame)
CV-40IE 40 W attenuator (without frame)	CV-40BE 40 W attenuator (without frame)	CV-40WE 40 W attenuator (without frame)	CV-40SE 40 W attenuator (without frame)
CV-60I 60 W attenuator (without frame)	CV-60B 60 W attenuator (without frame)	CV-60W 60 W attenuator (without frame)	CV-60S 60 W attenuator (without frame)
CV-PI 6-program selector (without frame)	CV-PB 6-program selector (without frame)	CV-PW 6-program selector (without frame)	CV-PS 6-program selector (without frame)
M-420I Framework	M-420B Framework	M-420W Framework	M-420S Framework

